

AMPCO Data Sheet

| | |
|------------------------|---|
| article# | A5272-9kv |
| article description | CEE-wall mounted plug 32A 7p 9h IP66/IP67 |
| description long | CEE-wall mounted plug 32A 7p 9h IP66/IP67 housing material: PA6 rated current: 32A number of poles: 7 (6P+PE) clock-position: 9h rated voltage/frequency: 220-250V~ / 50+60Hz contacts: brass nickel plated connection technology: screw terminals IP protection class: IP66/IP67 |
| GTIN (EAN) | 9003399398759 |
| country of origin | AT |
| customs number | 85366990 |
| net weight | 0.356 kg |
| packaging quantity | 5 |
| minimum order quantity | 10 |

| | |
|---------------------------------|-----------------------------|
| ETIM 9.0 | EC001319 |
| IEC-amperage | 32 A |
| Voltage according to EN 60309-2 | 200-250 V (50+60 Hz) blue |
| Number of poles | 7 |
| Clock hour position | 9 h |
| Identification colour | Blue |
| Degree of protection (IP) | IP67 |
| Connection system | Screwed terminal |
| Construction type | Surface mounted device plug |
| Angle of plug | Angled |
| Material | Plastic |
| Contact material | CuZn |
| Surface treatment contacts | Nickel-plated |

| | |
|------------------------|------------------------|
| a | 152 mm |
| b | 102 mm |
| c | 102 mm |
| wire flexible | 2,5-6 mm ² |
| wire solid | 2,5-10 mm ² |
| contact screws | 110 Ncm |
| connecting screws | 110 Ncm |
| dismantling length | 50 mm |
| stripping length | 12-14 mm |
| ambient temperature | -25 – 40 °C |
| temperature resistance | -25 – 80 °C |

