

article#	<b>A60232-9</b>
article description	<b>CEE-switched interlocked socket compact 32A 3p 9h IP66/IP67</b>
description long	CEE-switched interlocked socket compact 32A 3p 9h IP66/IP67 housing material: PA6 rated current: 32A number of poles: 3 (2P+PE) clock-position: 9h rated voltage/frequency: 380-415V~ / 50+60Hz contacts: brass nickel plated connection technology: screw terminals panel mounting, mechanical interlock switch: ON/OFF PCE-Merz ML0; EN 60947-3; AC22A, 10kA IP protection class: IP66/IP67
GTIN (EAN)	9003399476020
country of origin	AT
customs number	85366990
net weight	0.503 kg
packaging quantity	1
minimum order quantity	1

ETIM 9.0	EC001324
IEC-amperage	32 A
Number of poles	3
Voltage according to EN 60309-2	380-415 V (50+60 Hz) red
Clock hour position	9 h
Identification colour	Red
Degree of protection (IP)	IP67
Switch	Mechanical locking
Material housing	Plastic
Model	Top cover
Contact material	CuZn
Surface treatment contacts	Nickel-plated

a	67 mm
wire flexible	2,5-6 mm <sup>2</sup>
wire solid	2,5-10 mm <sup>2</sup>
contact screws	120 Ncm
ambient temperature	-25 – 40 °C
temperature resistance	-25 – 80 °C

