## **AMPCO Data Sheet**

| article#                | A6113-9k  |
|-------------------------|---|
| article description     | CEE-switched interlocked socket compact 16A 3p 9h IP44/IP54 knock-out   |
| description long        | CEE-switched interlocked socket compact 16A3p 9h IP44/IP54 knock-out housing material: PA6 + PC/ABS rated current: 16A number of poles: 3 (2P+PE) clock-position: 9h rated voltage/frequency: 380-415V~ / 50+60Hz contacts: brass nickel plated connection technology: screw terminals wall mounting housing with knock-out, mechanical interlock switch: ON/OFF PCE-Merz ML0; EN 60947-3; AC22A, 10kA IP protection class: IP44/IP54 |
| country of origin       | AT  |
| customs number          | 85366990  |
| packaging quantitiy     | 1   |
| minimum order quantitiy | 1   |

| ETIM 9.0                        | EC001324                 |
|---------------------------------|--------------------------|
| IEC-amperage                    | 16 A                     |
| Number of poles                 | 3                        |
| Voltage according to EN 60309-2 | 380-415 V (50+60 Hz) red |
| Clock hour position             | 9 h                      |
| Identification colour           | Red                      |
| Degree of protection (IP)       | IP54                     |
| Switch                          | Mechanical locking       |
| Material housing                | Plastic                  |
| Model                           | Base unit and cover      |
| Contact material                | CuZn                     |
| Surface treatment contacts      | Nickel-plated            |

| а                      | 115 mm      |
|------------------------|-------------|
| wire flexible          | 1,5-2,5 mm² |
| wire solid             | 1,5-4 mm²   |
| contact screws         | 120 Ncm     |
| housing screws         | 110 Ncm     |
| ambient temperature    | -25 – 40 °C |
| temperature resistance | -25 – 80 °C |





