

|                        |  |
|------------------------|--|
| article#               | <b>A6152-7</b>   |
| article description    | <b>CEE-flanged plug 75x75 straight 16A 5p 7h IP67</b>  |
| description long       | CEE-flanged plug 75x75 straight 16A 5p 7h IP67<br>housing material: PA6<br>rated current: 16A<br>number of poles: 5 (3P+N+PE)<br>clock-position: 7h<br>rated voltage/frequency: 277/480V~ - 288/500V~ / 50+60Hz<br>contacts: brass<br>connection technology: screw terminals<br>dimensions (flange/fixing center): 75x75 mm / 60x60 mm<br>IP protection class: IP66/IP67 |
| GTIN (EAN)             | 9003399495915  |
| country of origin      | AT   |
| customs number         | 85366990   |
| net weight             | 0.150 kg   |
| packaging quantity     | 10   |
| minimum order quantity | 10   |

|                                 |                        |
|---------------------------------|------------------------|
| ETIM 9.0                        | EC001319               |
| IEC-amperage                    | 16 A                   |
| Voltage according to EN 60309-2 | 500 V (50+60 Hz) black |
| Number of poles                 | 5                      |
| Clock hour position             | 7 h                    |
| Identification colour           | Black                  |
| Degree of protection (IP)       | IP67                   |
| Connection system               | Screwed terminal       |
| Construction type               | Built-up device plug   |
| Angle of plug                   | Straight               |
| Material                        | Plastic                |
| Contact material                | CuZn                   |
| Surface treatment contacts      | Untreated              |

|                        |                       |
|------------------------|-----------------------|
| a                      | 75 mm                 |
| b                      | 75 mm                 |
| c                      | 60 mm                 |
| d                      | 60 mm                 |
| e                      | 13 mm                 |
| f                      | 48 mm                 |
| g                      | 5,5 mm                |
| h                      | 55 mm                 |
| i                      | 87 mm                 |
| x                      | 5 mm                  |
| wire flexible          | 1-2,5 mm <sup>2</sup> |
| wire solid             | 1-4 mm <sup>2</sup>   |
| contact screws         | 100 Ncm               |
| dismantling length     | 50 mm                 |
| stripping length       | 10-12 mm              |
| ambient temperature    | -25 – 40 °C           |
| temperature resistance | -25 – 80 °C           |

