

AMPCO Data Sheet

| | |
|------------------------|--|
| article# | A734-6 |
| article description | CEE-flanged plug sloping 63A 4p 6h IP67 POWER TWIST |
| description long | CEE-flanged plug sloping 63A 4p 6h IP67 POWER TWIST housing material: PA6 rated current: 63A number of poles: 4 (3P+PE) clock-position: 6h rated voltage/frequency: 380-415V~ / 50+60Hz contacts: brass nickel plated, with pilot pin connection technology: frame terminals with screws dimensions (flange/fixing center): 100x112 mm / 80x88 mm IP protection class: IP66/IP67 |
| GTIN (EAN) | 9003399067822 |
| country of origin | AT |
| customs number | 85366990 |
| net weight | 0.566 kg |
| packaging quantity | 2 |
| minimum order quantity | 2 |

| | |
|---------------------------------|----------------------|
| ETIM 9.0 | EC001319 |
| IEC-amperage | 63 A |
| Voltage according to EN 60309-2 | 400 V (50+60 Hz) red |
| Number of poles | 4 |
| Clock hour position | 6 h |
| Identification colour | Red |
| Degree of protection (IP) | IP67 |
| Connection system | Screwed terminal |
| Construction type | Built-up device plug |
| Phase inverter | False |
| Angle of plug | Angled |
| Material | Plastic |
| Contact material | CuZn |
| Surface treatment contacts | Nickel-plated |

| | |
|------------------------|----------------------|
| a | 100 mm |
| b | 112 mm |
| c | 80 mm |
| d | 88 mm |
| e | 8 mm |
| f | 127 mm |
| g | 127 mm |
| h | 80 mm |
| i | 7 mm |
| wire flexible | 6-16 mm ² |
| wire solid | 6-25 mm ² |
| contact screws | 200 Ncm |
| connecting screws | 200 Ncm |
| dismantling length | 100 mm |
| stripping length | 15-18 mm |
| ambient temperature | -25 – 40 °C |
| temperature resistance | -25 – 80 °C |

