

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| article#               | <b>A7613-9</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| article description    | <b>CEE-switched interlocked socket DIN 16A 3p 9h IP44/IP54</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| description long       | CEE-switched interlocked socket DIN 16A 3p 9h IP44/IP54<br>housing material: PC/ABS<br>rated current: 16A<br>number of poles: 3 (2P+PE)<br>clock-position: 9h<br>rated voltage/frequency: 380-415V~ / 50+60Hz<br>contacts: brass nickel plated<br>connection technology: screw terminals<br>wall mounting, mechanical interlock, hinged window (5 modules), DIN-rail<br>switch: ON/OFF PCE-Merz ML0; EN 60947-3; AC22A, 10kA<br>cable entry: top, bottom or rear (incl. threaded blind cap)<br>IP protection class: IP44/IP54 |
| GTIN (EAN)             | 9003399847370                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| country of origin      | AT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| customs number         | 85366990                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| net weight             | 1,454 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| packaging quantity     | 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| minimum order quantity | 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

|                                  |                          |
|----------------------------------|--------------------------|
| ETIM 9.0                         | EC001324                 |
| IEC-amperage                     | 16 A                     |
| Number of poles                  | 3                        |
| Voltage according to EN 60309-2  | 380-415 V (50+60 Hz) red |
| Clock hour position              | 9 h                      |
| Identification colour            | Red                      |
| Degree of protection (IP)        | IP54                     |
| Switch                           | Mechanical locking       |
| Empty locations on mounting rail | True                     |
| Material housing                 | Plastic                  |
| Model                            | Base unit and cover      |
| Protection                       | None                     |
| Contact material                 | CuZn                     |
| Surface treatment contacts       | Nickel-plated            |

|                        |                         |
|------------------------|-------------------------|
| a                      | 359 mm                  |
| b                      | 153 mm                  |
| wire flexible          | 1,5-2,5 mm <sup>2</sup> |
| wire solid             | 1,5-4 mm <sup>2</sup>   |
| contact screws         | 120 Ncm                 |
| housing screws         | 110 Ncm                 |
| ambient temperature    | -25 – 40 °C             |
| temperature resistance | -25 – 80 °C             |

