

| | |
|------------------------|---|
| article# | A7614-9 |
| article description | CEE-switched interlocked socket DIN 16A 4p 9h IP44/IP54 |
| description long | CEE-switched interlocked socket DIN 16A 4p 9h IP44/IP54 housing material: PC/ABS rated current: 16A number of poles: 4 (3P+PE) clock-position: 9h rated voltage/frequency: 200-250V~ / 50+60Hz contacts: brass nickel plated connection technology: screw terminals wall mounting, mechanical interlock, hinged window (5 modules), DIN-rail switch: ON/OFF PCE-Merz ML0; EN 60947-3; AC22A, 10kA cable entry: top, bottom or rear (incl. threaded blind cap) IP protection class: IP44/IP54 |
| GTIN (EAN) | 9003399587139 |
| country of origin | AT |
| customs number | 85366990 |
| net weight | 1,469 kg |
| packaging quantity | 1 |
| minimum order quantity | 1 |



| | |
|----------------------------------|---------------------------|
| ETIM 9.0 | EC001324 |
| IEC-amperage | 16 A |
| Number of poles | 4 |
| Voltage according to EN 60309-2 | 200-250 V (50+60 Hz) blue |
| Clock hour position | 9 h |
| Identification colour | Blue |
| Degree of protection (IP) | IP54 |
| Switch | Mechanical locking |
| Empty locations on mounting rail | True |
| Material housing | Plastic |
| Model | Base unit and cover |
| Protection | None |
| Contact material | CuZn |
| Surface treatment contacts | Nickel-plated |

| | |
|------------------------|-------------------------|
| a | 359 mm |
| b | 153 mm |
| wire flexible | 1,5-2,5 mm ² |
| wire solid | 1,5-4 mm ² |
| contact screws | 120 Ncm |
| housing screws | 110 Ncm |
| ambient temperature | -25 – 40 °C |
| temperature resistance | -25 – 80 °C |

