

article#	<b>A9029100</b>
article description	<b>CEE-Steckdose abschaltbar Sölden IV 125A 5p 6h M63oBVu Lastt.4pEa</b>
description long	thermoplastic distribution box - wall mounted - model Sölden IP66 520x297x165 13TE with external wall mounting brackets 1xM63 cable gland on top (cable diameter 34-44mm PG48) black 1x blind cable gland M63 from bottom 1xCEE-socket 125A 5p 400V with PCS system protected with circuit breaker 125A4p with integrated low voltage circuit breaker (for 125A) control circuit protected with MCB 2A 2p C MCB made by Eaton OVE / VDE circuit breaker made by Eaton OVE / VDE TYP NZM1 thermic release distribution box is wired on terminals 5x50qmm task: Through the PCS system in connection with the switch disconnecter including undervoltage release will be the tension-free plugging and pulling on the socket 125A guaranteed in addition the sockets are secured against automatic resetting after power failure of the supply line.
GTIN (EAN)	9003399981333
country of origin	AT
customs number	85371098
net weight	10.000 kg
packaging quantity	1
minimum order quantity	1

ETIM 9.0	EC001324
IEC-amperage	125 A
Number of poles	5
Voltage according to EN 60309-2	400 V (50+60 Hz) red
Clock hour position	6 h
Identification colour	Red
Degree of protection (IP)	IP54
Switch	Electrical locking
Material housing	Plastic
Model	Base unit and cover
Contact material	CuZn
Surface treatment contacts	Nickel-plated

wire flexible	16-50 mm <sup>2</sup>
wire solid	16-70 mm <sup>2</sup>

