

AMPCO Data Sheet

article#	A9350001-p
article description	XREEL310 4xSSD54+L 40m3G2.5H07 PS30 K2
description long	<p>Cable Reel XREEL310 Reel (black) with central, internal locking mechanism Protected connecting area Solid carrying rack (black) with ergonomic handle Central plate with 4 pcs safety machine sockets national version with self-closing hinged lids and sealing edge (105-0bsw) Rated operating voltage: 250V Rated current: 16A Protection rating: IP54 1 pcs power supply light 40m Black cable H07RN-F 3G2.5mm2 TopTaurus2 safety plug 16A 2p+PE 2SL 250V IP54 (05721-sr) Cable reel installed ready for use complies with RoHS directive 2011/65/EU low voltage directive NSpRI 2014/35/EU UV stability according ISO 4892-2 acc standard IEC/EN 61242 Protection rating complete system: IP54 Conform with BGI608 K2</p>
GTIN (EAN)	9003399328510
country of origin	PL
customs number	85444290
net weight	10.600 kg
packaging quantity	1
minimum order quantity	1

ETIM 9.0	EC000003
Number of poles	3
Rated voltage	230 V
Rated current	16 A
Rated fault current	0.03 A
Mounting method	Other
Leakage current type	Other
Frequency	50 Hz
Degree of protection (IP)	IP54

